



another innovation from...NEWHOME BATH & MIRROR, INC.

Product Specifications

Overview

The Original ClearMirror™ is an electrical bathroom mirror defogger. Simply speaking, a ClearMirror™ is a very thin heater that is adhered to the back of a mirror and wired to the same power supply as the bathroom light fixture, fan or separate switch. When turned on the pad heats up, preventing condensation on the surface of the mirror. The size of the ClearMirror determines the area of the mirror that will remain dry and fog free. Depending upon humidity and time, the heat will radiate and may clear a larger area. Do not install on exterior walls.

Important ClearMirror™ features:

- Safety Tested: UL and C-UL listed (tested to CSA international standards)
- Warranty: 5-year replacement against product defect
- Durability: Same heater used in industrial applications for over 25-years.

Technical Specifications

The heater is a uniform grid of wires fused between two layers of silicone rubber sheets.

- Adhesion to Mirror: Pre-applied 3M Acrylic PSA with removable contact paper
- Pad Thickness: 1/16" to 1/8"
- Power Supply: 120-Volts (also available in 12, 24, 127 and 240-volts)
- Standard Sizes and Wattage: 8"x10"-14 watts, 12"x12"-26 watts, 14"x14"-35 watts, 16"x16"-45 watts, 18"x20"-65 watts (custom shapes and sizes available in volume).
- Connection: Standard 2-48" silicone wire leads that exit the ClearMirror from the top center edge. Optional connections: ALCI Cordset (plug), Romex Cable (14-gauge non-sheathed cable) and low-voltage transformer with silicone wire leads.

Questions and Installation Instructions: www.clearmirror.com or, 877.242.5327

Request for Quotes: Fax-651.739.0403 or, E-mail-Sales@ClearMirror.com



The Original ClearMirror™